

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

10/506816

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
12 September 2003 (12.09.2003)


PCT

(10) International Publication Number
WO 03/074130 A1

- (51) International Patent Classification⁷: A62B 17/04, (74) Agent: REINHOLD COHN AND PARTNERS; P.O. Box 4060, 61040 Tel Aviv (IL).
23/02
- (21) International Application Number: PCT/IL03/00148 (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (22) International Filing Date: 26 February 2003 (26.02.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 148504 5 March 2002 (05.03.2002) IL (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- (71) Applicant and
(72) Inventor: REISMAN, Ron (IL/IL); Kibbutz Netzez Sireni, 70395 D.N. Beer Yaacob (IL).

[Continued on next page]

(54) Title: PROTECTIVE BREATHING HOOD



(57) Abstract: A protective breathing hood comprising a hood made of a stretchable fire resistant material and which is also impermeable to gases and biologic material. The hood is sized and shaped for placing over a head of a user in an airtight manner with an opening of the hood sealingly engaging a neck portion of the user. At least a visor portion of the hood is transparent and a pair of respiratory units are disposed offset with respect to the nose location. Each respiratory unit comprises a housing formed with an inhalation flow path accommodating activated charcoal particles, and an exhalation flow path fitted with a one way exhaling valve, wherein at a donned position of the hood a chamber is formed at a mouth/nose location thereof.

WO 03/074130 A1